

# TECH DATA SHEET

# PROJOINT

# PRO420ECO

# ENHANCING SEALER

WATER BASED

PROSEAL TECHNOLOGY



### PREPARATION:

PAVING SHOULD BE COMPLETELY DRY, CLEAN AND FREE FROM DIRT, DUST, OIL, ETC. WE RECOMMEND CLEANING WITH PROJINT ULTIMATE PAVING CLEANER PRIOR TO APPLICATION. AVOID APPLICATION DURING EXTREME TEMPERATURE CONDITIONS; IDEALLY, WHEN THE SURFACE TEMPERATURE IS BETWEEN 5°C TO 25°C.

### APPLICATION INSTRUCTIONS:

**1:** SHAKE THE CONTAINER BEFORE USE. **2:** WEARING APPROPRIATE PPE, APPLY THE PROJINT PRO-420 ECO EVENLY USING A FOAM ROLLER, PAINT BRUSH, OR A LOW-PRESSURE SPRAYER. **3:** DEPENDING ON THE SURFACE POROSITY, APPLY EXTRA COATS IN HOURLY INTERVALS UNTIL THE PAVING IS FULLY SATURATED. **4:** ALL TOOLS/EQUIPMENT SHOULD BE THOROUGHLY CLEANED WITH WATER AFTER USE.

**IMPORTANT:** ALWAYS TEST IN A HIDDEN AREA PRIOR TO USE AND ONLY PROCEED WHEN SATISFIED WITH THE RESULTS. THE TECHNICAL INFORMATION SUPPLIED IS BASED ON DATA OBTAINED BY OUR OWN RESEARCH AND IS CONSIDERED ACCURATE. HOWEVER, NO LIABILITY IS ACCEPTED FOR ANY LOSS OR DAMAGE ARISING DIRECTLY OR INDIRECTLY FROM THE USE OF OUR PRODUCTS, OR FROM THE INFORMATION GIVEN IN PUBLICATIONS. PROSPECTIVE USERS SHOULD THEREFORE SATISFY THEMSELVES BY APPROPRIATE TRIALS THAT THE PRODUCT IS SUITABLE FOR THE INTENDED USE. DO NOT DISCHARGE WASTE INTO DRAINS OR RIVERS.

SYSTEM	WATER BASED SEALER
STORAGE	STORE IN A COOL, AND DRY AT TEMPERATURES BETWEEN 5°C AND 25°C
SHELF LIFE	12 MONTH FROM DATE OF MANUFACTURE
PACKAGING	1LTR, 5LTR AND 25LTR CONTAINERS
DRYING TIME	60 MINUTES IN DRY AMBIENT CONDITIONS
COVERAGE	APPROXIMATELY 12SQM PER LTR



### WARNING

KEEP OUT OF REACH OF CHILDREN. DISPOSE OF CONTENTS/CONTAINER TO A LICENSED WASTE CENTRE IN ACCORDANCE WITH LOCAL/REGIONAL/NATIONAL/ INTERNATIONAL REGULATIONS.

## KEY FACTS:

- ✓ ENHANCED NATURAL LOOK FINISH
- ✓ IMPREGNATES THE SURFACE OF THE STONE FOR LASTING PROTECTION AGAINST WATER-PENETRATION, STAINING AND NATURAL WEATHERING
- ✓ WATER-BASED - CAN BE USED ALL YEAR ROUND
- ✓ HIGH COVERAGE RATE (AVERAGE OF 12M2 PER LITRE)
- ✓ PERFECT FOR ALL TYPES OF NATURAL STONE OR CONCRETE PAVING

## BRUTE STRENGTH PAVING PRODUCTS

